










1	2	3	4	5	6	7	8
RoHS Compliant		REVISIONS					
					REV.	DESCRIPTION	DATE
							DESIGN
A				NOTES: 1. MATERIAL: 1-1.HOUSING:LCP,UL94V-0,COLOR:BLUE 300C; 1-2.CONTACT:C7025 (T=0.20MM.) ; 1-3.SHELL:SUS201 (T=0.3MM.); 2. PLATING: 2-1.CONTACT: CONTACT AREA: GOLDFLASH MATTE Tin 60u" MIN PLATED ON SOLDER TAILS Ni 30u" MIN UNDERPLATED. 2-2.SHELL: Ni 30u" MIN PLATED OVER ALL 3. MECHANICAL CHARACTERISTIC 3-1.MATING FORCE: 35N MAX 3-2.UNMATING FORCE: INITIAL:10N Min AFTER TEST:8N Min 3-3.DURABILITY: 5000 CYCLES. 4. ELECTRICAL CHARACTERISTIC 4-1.CONTACT CURRENT RATING:1.8A FOR PIN1&PIN4. 0.25A FOR OTHER CONTACTS 4-2.LOW LEVEL CONTACT RESISTANCE: INITIAL: 30mΩ MAX FOR VBUS AND GND 50mΩ MAX FOR ALL OTHER CONTACTS 4-3.INSULATION RESISTANCE: 100MΩ MIN 4-4.DELECTIC WITHSTANDING VOLTAGE: 100VAC R.M.S 5. TEMPERATURE OPERATING TEMPERATURE: -40°C~+85°C 6. RECOMMENDED PROCESS:IR REFLOW 260+0/-5°C 5S; 7. SALT SPRAY:24H			
B							
C							
D							
PART NO. INFORMATION U03-A F X A X X -3015							
PORT TYPE A: TYPE A		PACKAGE T: TRAY R:TAPE REEL					
GENDER F: FEMALE M: MALE		HOUSING COLOR 2: WHITE 5: BLACK 9: BLUE					
CONTACT PLATED 1: GOLD FLASH 2: GOLD 3U" 3: GOLD 5U" 4: GOLD 10U" 5: GOLD 15U" 6: GOLD 30U"		HOUSING MATERIAL A: LCP B: PBT C: PA9T D: PA6T E: PA46 F: PA66					
Bestcreate Technology Limited							
TOLERANCES UNLESS OTHERWISE SPECIFIED:				DESIGN: I.L		DATE: 2017.3.1	
X. ± 0.30 X* $\pm 3^{\circ}$.X ± 0.20 .X* $\pm 2^{\circ}$.XX ± 0.15 .XX* $\pm 1^{\circ}$				CHECKED: C.W		DATE: 2017.3.1	
Website: www.bsc-elec.com E-mail: bestcreate@bsc-elec.com				APPROVED: C.W		DATE: 2017.3.1	
REV: A	UNIT mm	SCALE 1=1	QUALITY SYMBOLS			FINSH:	DWG NO: U03-AFXAXX-3015
1	2	3	4	5	6	7	SHEET: 1 OF 2


RoHS Compliant

350PCS/REEL
每盘装产品数量

用胶带将防水袋封口, 然后在外箱的四角各放一个护角板.

在外箱内套入一个
防水袋, 然后将装满产
品的10盘卷盘放入箱内.
每箱装10盘, 共计产
品3500PCS.

350X350X305mm



C

D

Bestcreate Technology Limited

REV: A UNIT mm SCALE 1=1 QUALITY SYMBOLS

TOLERANCES UNLESS OTHERWISE SPECIFIED:

X.	± 0.30	X.	± 3°
.X	± 0.20	.X"	± 2°
.XX	± 0.15	.XX"	± 1°

Website: www.bsc-elec.comE-mail: bestcreate@bsc-elec.com

DESIGN: I.L DATE: 2017.3.1

CHECKED: C.W DATE: 2017.3.1

APPROVED: C.W DATE: 2017.3.1

TITLE: USB3.0 A/F 9PIN R/A SMT CH=2.86 L=11.5

MATERIAL: PART NO: U03-AFXAXX-3015 SIZE: A4

FINSH: DWG NO: U03-AFXAXX-3015 SHEET: 2 OF 2