

RoHS Compliant

REVISIONS

REV.	DESCRIPTION	DATE	DESIGN

NOTE:

1.MATERIAL:

Housing: Pa66.BLACK. Thermo plastics,UL94V-0.

Contact:Copper Alloy.

Shell: SUS 304

2.Electrical performance:

Voltage Current Rating:1.5 AMP. 30V AC

Insulation Resistance:1000MΩ Min.

Contact Resistance:30 mΩ Max.

Dielectric Withstanding Voltage:500V AC

3.Temperature Range:-40℃ to +85℃

4.FINISH:

Contact:Tin Plating 100u" on solder tail area,
RJ45 Phosphor Bronze, 6u" Gold plated.

USB Phosphor Bronze, 1u" Gold plated.

TYPE C Phosphor Bronze, 1u" Gold plated.

Ni underplating over all.

PART NO. INFORMATION

U3120RJ01- X 5 0 X - 016

CONTACT PLATED

1: G/F 2: AU 3U"
3: AU 6U" 4: AU 15U"
5: AU 30U"

PACKAGE

R: TAPE REEL
T: TRAY

Bestcreate Technology Limited

TOLERANCES UNLESS OTHERWISE SPECIFIED:

.X	± 0.35	X.*	± 3"
.XX	± 0.25	.X.*	± 2"
.XXX	± 0.15	.XX.*	± 1"

Website:www.bsc-elec.com

Email:bestcreate@bsc-elec.com

DESIGN:

DATE:

I. L

2017. 3. 1

CHECKED:

DATE:

C. W

2017. 3. 1

APPROVED:

DATE:

C. W

2017. 3. 1

TITLE:

RJ45+SIDE-ENTRY USB2. 0+SIDE ENTRY TYPE C CONNECTOR

MATERILA:

PART NO:

U312RJ01-X50X-016

SIZE:

A4

FINSH:

DWG NO:

U312RJ01-X50X-016

1of1