



RoHS Compliant

REVISIONS

REV.	DESCRIPTION	DATE	DESIGN

- 1.MATERIAL SPECIFICATION:
1.1.STAINLESS STEEL SUS-301 T=0.15±0.005MM
- 2.TEST REQUIREMENTS:
2.1.CONTACT RESISTANCE: 80mΩ MAX
2.2.VOLTAGE RATING: 1.5 V/AC/DC/MAX
2.3.RATED CURRENT: 1.0A/MAX
2.4.CLAMPING FORCE: 60g-120g
2.5.WELDING THRUST: ≥3.0 Kg
2.6.DURABILITY: 20000 TIMES
2.7.OPERATING TEMPERATURE: -20 ° ~ 80 ° C
- 3.PLATING REQUIREMENTS:
3.1.OVERALL NICKEL PLATING 50U MIN,
OVERALL MIST TIN PLATING 30U MIN
3.2.SALT SPRAY TEST TO MEET THE REQUIREMENTS OF 24 HOURS.
3.3.TERMINAL TO EAT FULL TIN, NOT PEELING, WELDING,
OBVIOUS COLOR AND OTHER ADVERSE
3.4.ROHS, REACH, HF HALOGEN-FREE AND A SERIES
OF DOMESTIC AND INTERNATIONAL ENVIRONMENTAL
REQUIREMENTS



Bestcreate Technology Limited

TOLERANCES UNLESS OTHERWISE SPECIFIED:

X.	±	0.25	X.*	±	3"
.X	±	0.20	.X*	±	2"
.XX	±	0.15	.XX*	±	1"

Website:www.bsc-elec.com
Email:bestcreate@bsc-elec.com

DESIGN: I. L DATE: 2017. 3. 1
CHECKED: C. W DATE: 2017. 3. 1
APPROVED: C. W DATE: 2017. 3. 1

TITLE: 2. 9*1. 7*1. 65H
(B TYPE)Wire clip

MATERILA:	PART NO: AS-R5-098-0016B	SIZE: A4
FINSH:	DWG NO: AS-R5-098-0016B	

REV: A	UNIT mm	SCALE 1=1	QUALITY SYMBOLS
--------	---------	-----------	-----------------