






RoHS Compliant


REVISIONS

REV.	DESCRIPTION	DATE	DESIGN



P.C.B LAYOUT
TOLERANCE:±0.05

- MATERIAL SPECIFICATION:
 - C5210 T=0.10±0.005MM
- TEST REQUIREMENTS:
 - CONTACT RESISTANCE: 80mΩ MAX
 - VOLTAGE RATING: 1.5 V/AC/DC/MAX
 - RATED CURRENT: 1.0A/MAX
 - WELDING THRUST: ≥3.0 Kg
 - DURABILITY: 1,500 TIMES
 - OPERATING TEMPERATURE: -20 ° ~ 80 ° C
- PLATING REQUIREMENTS:
 - OVERALL NICKEL PLATING 50U MIN, WELDING SURFACE 1U MIN GOLD PLATING, CONTACT AREA 3U MIN GOLD PLATING
 - SALT SPRAY TEST TO MEET THE REQUIREMENTS OF 24 HOURS.
 - TERMINAL TO EAT FULL TIN, NOT PEELING, WELDING, OBVIOUS COLOR AND OTHER ADVERSE
 - ROHS, REACH, HF HALOGEN-FREE AND A SERIES OF DOMESTIC AND INTERNATIONAL ENVIRONMENTAL REQUIREMENTS



Bestcreate Technology Limited

TOLERANCES UNLESS OTHERWISE SPECIFIED:

X.	±	0.25	X.*	±	3'
.X	±	0.20	.X'	±	2'
.XX	±	0.15	.XX'	±	1'

Website:www.bsc-elec.com
Email:bestcreate@bsc-elec.com

DESIGN: I. L
DATE: 2017. 3. 1

CHECKED: C. W
DATE: 2017. 3. 1

APPROVED: C. W
DATE: 2017. 3. 1

TITLE: Antenna Shrapnel Connector
1. 90*1. 00*2. 60H (B TYPE)

MATERILA:	PART NO: AS-R5-098-0026B	SIZE: A4
FINSH:	DWG NO: AS-R5-098-0026B	

REV: A	UNIT mm	SCALE 1=1	QUALITY SYMBOLS
--------	---------	-----------	-----------------