



RoHS Compliant

REVISIONS

REV.	DESCRIPTION	DATE	DESIGN



1. MATERIAL SPECIFICATION:
1.1. STAINLESS STEEL SUS-304 T=0.10±0.005MM
2. TEST REQUIREMENTS:
2.1. CONTACT RESISTANCE: 80mΩ MAX
2.2. VOLTAGE RATING: 1.5 V/AC/DC/MAX
2.3. RATED CURRENT: 1.0A/MAX
2.4. WELDING THRUST: ≥3.0 Kg
2.5. DURABILITY: 1,500 TIMES
2.6. OPERATING TEMPERATURE: -20 ° ~ 80 ° C
3. PLATING REQUIREMENTS:
3.1. OVERALL NICKEL PLATING 50U MIN, WELDING SURFACE 1U MIN GOLD PLATING, CONTACT AREA 1U MIN GOLD PLATING
3.2. SALT SPRAY TEST TO MEET THE REQUIREMENTS OF 24 HOURS.
3.3. TERMINAL TO EAT FULL TIN, NOT PEELING, WELDING, OBVIOUS COLOR AND OTHER ADVERSE
3.4. ROHS, REACH, HF HALOGEN-FREE AND A SERIES OF DOMESTIC AND INTERNATIONAL ENVIRONMENTAL REQUIREMENTS



Bestcreate Technology Limited

REV: A UNIT mm SCALE 1=1 QUALITY SYMBOLS

TOLERANCES UNLESS OTHERWISE SPECIFIED:

X.	±	0.25	X.*	±	3"
.X	±	0.20	.X*	±	2"
.XX	±	0.15	.XX*	±	1"

Website: www.bsc-elec.com
Email: bestcreate@bsc-elec.com

DESIGN: I. L DATE: 2017. 3. 1

CHECKED: C. W DATE: 2017. 3. 1

APPROVED: C. W DATE: 2017. 3. 1

TITLE: Antenna Shrapnel Connector
3. 50*1. 50*3. 55H(A TYPE)

MATERIAL:	PART NO: AS-R5-098-0035A	SIZE: A4
FINISH:	DWG NO: AS-R5-098-0035A	