


RoHS Compliant

Features:
 1.2~8 circuits available;
 2.Material: PA46 UL 94V-0
 3.Accepts H250011-XX terminal;
 4.Mates with H2500S13,H2500S14;
 5.Coloe: Black/Natural

Specification:


Current rating: 8A at 10A .
 Voltage rating: 400V AC(RMS) or 400V DC Max.
 Contact resistance: 10mΩ Max.
 Insulation resistance: 100MΩ Min.
 Withstanding voltage: 1800VAC/minute.
 Ambient temperature range: -40°C~105°C.
 Dimensional infotmation(mm)

Circuits	DIM A	DIM B
2	7.70	2.50
3	10.20	5.00
4	12.70	7.50
5	15.20	10.00
6	17.70	12.50
7	20.20	15.00
8	22.70	17.50



PART NO. INFORMATION

H2500S12-XX-X
 SERIES NO:
 PIN Q' PY:
 02~08
 A-BLACK (KEY A)
 B-NATURE (KEY B)



Bestcreate Technology Limited

REV: A UNIT mm SCALE 1=1 QUALITY SYMBOLS

TOLERANCES UNLESS OTHERWISE SPECIFIED:

$X \pm 0.40$	$X' \pm 3^\circ$
$.XX \pm 0.25$	$.X' \pm 2^\circ$
$.XXX \pm 0.15$	$.XX' \pm 1^\circ$

Website: www.bsc-elec.com

Email: bestcreate@bsc-elec.com

DESIGN: I. L DATE: 2018.3.5
 CHECKED: C. W DATE: 2018.3.5
 APPROVED: C. W DATE: 2018.3.5

TITLE: 2.5 mm single row wire to Board housing
 MATERIAL: H2500S12-XX-X SIZE: A4
 FINSH: DWG NO: H2500S12-XX-X